

PURE CLICK TECHNICAL DATA



Board: 1326 x 204 mm – Box: 8 boards (= 2,164 m²) – Pallet: 56 boxes (= 121,186 m²)
Board XXL: 1836 x 204 mm – Box: 6 boards (= 2,247 m²) – Pallet: 56 boxes (= 125,847 m²)
Tile: 612 x 612 mm – Box: 6 tiles (= 2,247 m²) – Pallet: 28 boxes (= 62,923 m²)
Tile: 612 x 306 mm – Box: 8 tiles (= 1,498 m²) – Pallet: 56 boxes (= 83,898 m²)

PRODUCT SPECIFICATION		CLICK 40	CLICK 55
Total thickness	EN ISO 24346	5 mm	5 mm
Wear layer	EN ISO 24340	0,40 mm	0,55 mm
Total weight	EN ISO 23997	5,73 kg/ m²	5,73 kg/ m²
Surface treatment		PUR	PUR
Usage classification	EN ISO 10874	23-32	23-33
TEST RESULTS			
Underfloor heating	EN ISO 12524	suitable max. 27°C (80°F) / electrical floor heating systems: max 60 W/m²	
Castor chair	EN ISO 4918	pass	pass
Fire resistance	EN ISO 13501-1	Bfl-s1	Bfl-s1
Chemical resistance	EN ISO 26987	OK	OK
Thermal resistance	EN EN ISO 8302	0,041 m² K/W	0,041 m² K/W
Residual indentation	EN ISO 24343-1	< 0,10 mm/ 4 %	< 0,10 mm/ 4 %
Slip resistance	DIN 51130 EN ISO 13983	R11 class DS	R11 class DS
RRL Pendulum test (wet test 4S Rubber/Slider 96)		≥ 0,36	≥ 0,36
Sound reduction: Impact Sound	EN ISO 717-2 (Δ Lw)	10 dB	10 dB
Reflected Walking Sound	EPLF draft 021029-5 F1	*** (9,7 sone)	*** (9,7 sone)
Light fastness	EN ISO 105-B02	> 6	> 6
Dimensional stability	EN ISO 23999	<0,25%	<0,25%
Antistatic	EN ISO 1815	yes	yes
Residential warranty		Lifetime	Lifetime
Commercial warranty		-	10 years
Formaldehyde	EN ISO 717-1	E1	E1
U-label		DIBT approval no. Z-156.603-1525	



Version published on 07/2017.
Replaces all previous versions.
This specification is based on the technical knowledge at the time of creation / publication, and can be modified, supplemented or replaced at any time. Check for updates on www.berryalloc.com

